


LED Bollard - IL-BOSF Series (Square, Flat Top)

FEATURES & SPECIFICATION SHEET





Application

The IL-BOSF Series outdoor bollard fixture is specifically designed to provide consistent light quality in a durable Stainless Steel housing. Modern Design and Highest Quality. Ideal for retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities.

Features

- 42" Standard Height Bollard Area Light
- Lens Options: Cone Reflector, Glass Reflector,
 Louvered Lens
- Bronze Powder Coat Finish
- CSA listed
- IP65 for wet locations

LED & Driver

A long lifetime rating of 50,000 hours or about 10 years operating hours 12 hours per 7 days per week. LED and Driver features Class P rating, THD of less than 10, constant output wattage, and a fail-safe protection.

Warranty

Guaranteed for 5 years against manufacturing defects.

MODEL	COLOR TEMP	WATTS	RETROFIT WATTS	LUMENS	DIMENSIONS
IL-BOSFRLQ	5000k	15w	Up to 70w	1167lm	See Diagram
IL-BOSFG3Q	5000k	15w	Up to 70w	1167lm	See Diagram
IL-BOSFLSQ	5000k	15w	Up to 70w	1167lm	See Diagram

(*Available Color Temp Range 3000k – 6500k (Warm – Cool) on request.)

Toll Free: 855-453-2852 | Email: info@inductionlightingfixtures.com