




ILWR40 LED Wrap Around

FEATURES & SPECIFICATION SHEET



Application

Cost-effective and energy efficient 4ft LED utility wrap fixture. Ideal replacement for less efficient fluorescent wrap fixtures. Perfect for: Storage areas, Utility rooms, Schools, Stairwell, Workshops, Corridors

Features

- 4ft LED utility wrap fixture
- 130 Lms/Watt
- Full length wrap-around U-shaped prismatic acrylic lens
- Universal 0-10V driver for continuous dimming standard
- Durable steel body construction with white polyester powder coat finish
- 50,000 hour designed minimum lifetime
- Ambient operating temperature: -20°C (-4°F) to 50°C (122°F)
- CRI: >80 • 120-277V Universal Voltage
- Power Factor: >.9 • THD: <20%
- UL / DLC Listed

LED PCB & Driver

A long lifecycle rating of 50,000 hours

Warranty

Lamp is guaranteed for 5 years against manufacturing defects.

Ordering Information
ILWR40 - - 4K -
Model Color

MODEL	*COLOR TEMP	VOLTS L - 120-277V	WATTS	LUMENS	DIMENSIONS LxWxH
ILWR-40	3500k 4000k 5000k	L	40w	5240	2.8"48"x7.1"